

View Online at <https://aerobasegroup.com/nsn/5910-00-547-8513>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

Between 0.154 inches and 0.159 inches

Terminal Length:

Between 0.125 inches and 0.155 inches

Body Length:

Between 0.330 inches and 0.350 inches

Continuous Current Rating In Amps:

10.0

Terminal Diameter:

Between 0.022 inches and 0.042 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

5000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-56.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-0.00/+100.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

500.0 megohms

Dissipation Factor At Reference Temperature In Percent:

3.0000

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0