NSN 5910-00-549-2466

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-549-2466

| Body Style: |
|--|
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Established |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| Between 0.336 inches and 0.367 inches |
| Body Length: |
| 0.786 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Electrical Polarization: |
| Polarized |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 33.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 35.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Tantalum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 6.0000 |
| Dc Leakage At Reference Temp: |
| 11.000 microamperes |
| Case Insulation Material: |
| Plastic |
| Test Data Document: |
| 81349-milc39003/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

N/a

Shelf Life:

NSN 5910-00-549-2466

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0