NSN 5910-00-550-1698

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-550-1698

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.274 inches and 0.305 inches **Body Length:** 0.686 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 100.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 15.000 microamperes **Case Insulation Material:** Plastic **Test Data Document:** 81349-milc39003/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-550-1698

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0