NSN 5910-00-552-1226

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-552-1226

D. J. O. J.
Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established
Body Length:
3.375 inches
Body Width:
3.375 inches
Body Height:
4.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.625 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.625 inches
Mounting Facility Screw Thread Series Designator:
Uns
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded mounting studs
4 threaded mounting studs
4 threaded mounting studs Features Provided:
4 threaded mounting studs Features Provided: Hermetically sealed case
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section:
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp:
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size:
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section:
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section:
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: -20.00/+20.00 microfarads single section
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: -20.00/+20.00 microfarads single section Case Material:
4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: -20.00/+20.00 microfarads single section Case Material: Metal

2 tab, solder lug

NSN 5910-00-552-1226

Electrolytic Fixed Capacitor - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0