NSN 5910-00-552-1226

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-552-1226

| D. J. O. J. |
|--|
| Body Style: |
| W/thd mtg hol (s)/stud(s) terminal(s) on one surface |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 3.375 inches |
| Body Width: |
| 3.375 inches |
| Body Height: |
| 4.000 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.625 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Polarized |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 2.625 inches |
| Mounting Facility Screw Thread Series Designator: |
| Uns |
| |
| Mounting Facility Type And Quantity: |
| Mounting Facility Type And Quantity: 4 threaded mounting studs |
| |
| 4 threaded mounting studs |
| 4 threaded mounting studs Features Provided: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: -20.00/+20.00 microfarads single section |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: -20.00/+20.00 microfarads single section Case Material: |
| 4 threaded mounting studs Features Provided: Hermetically sealed case Capacitance Value Per Section: 400.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.594 inches Nonderated Continuous Voltage Rating And Type Per Section: 165.0 dc single section Tolerance Range Per Section: -20.00/+20.00 microfarads single section Case Material: Metal |

2 tab, solder lug

NSN 5910-00-552-1226

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0