

View Online at <https://aerobasegroup.com/nsn/5910-00-553-6936>

Body Style:

Piston

Overall Length:

Between 0.718 inches and 0.749 inches

Terminal Length:

0.719 inches

Body Length:

Between 0.532 inches and 0.594 inches

Overall Diameter:

0.250 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Center To Center Distance Between Terminals Parallel To Length:

Between 0.407 inches and 0.469 inches

Terminal Diameter:

0.020 inches

Quality Factor At 25 Deg Celsius:

500.0

Fragility Factor:

Moderately rugged

Terminal Width:

0.141 inches

Terminal Thickness:

0.020 inches

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+0.8/+8.5 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.04 single section

Material:

Glass inclosure

Precious Material And Location:

Metal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

1 tab, solder lug and 1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0