

View Online at <https://aerobasegroup.com/nsn/5910-00-553-7036>

Thread Class:

2a

Body Style:

Piston

Bushing Diameter:

Any acceptable

Bushing Length:

Any acceptable

Body Length:

1.000 inches

Overall Diameter:

0.400 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

+350.0 to 450.0 single section

Quality Factor At 25 Deg Celsius:

500.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 5.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+0.8 to 18.0 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

1 wire lead and 1 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0