NSN 5910-00-553-7036

Glass Dielectric Variable Capacitor - Page 1 of 2



1
View Online at https://aerobasegroup.com/nsn/5910-00-553-7036
Thread Class:
2a
Body Style:
Piston
Bushing Diameter:
Any acceptable
Bushing Length:
Any acceptable
Body Length:
1.000 inches
Overall Diameter:
0.400 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
+350.0 to 450.0 single section
Quality Factor At 25 Deg Celsius:
500.0
Mounting Facility Screw Thread Series Designator:
Unef
Inclosure Type:
Encapsulated
Adjustment Device Torque:
Between 1.000 inch-ounces and 5.000 inch-ounces
Bushing Shape:
Round
Insulation Dc Resistance At 25 Deg Celsius:
1000.0 gigohms
Mounting Facility Type And Quantity:
1 threaded bushing
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.250 inches
Capacitance Range In Picofarads:
+0.8 to 18.0 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 wire lead and 1 screw

Shelf Life: N/a

NSN 5910-00-553-7036

Glass Dielectric Variable Capacitor - Page 2 of 2



	• •					
ın	18	<i>(</i>)+	Me	20	III	ω.

--

Demilitarization:

No

Fiig:

A096a0