## NSN 5910-00-556-9136

**Body Style:** 

W/thd mtg studs, axial terminals

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-556-9136

| Reliability Indicator:   |
|--|
| Not established  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.670 inches   |
| Body Length:   |
| 1.624 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.875 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Internal Electrical Connection Type:   |
| Extended foil  |
| Mounting Facility Screw Thread Series Designator:                            |
| Unc  |
| Mounting Facility Type And Quantity:   |
| 2 threaded mounting studs  |
| Features Provided:   |
| Hermetically sealed case   |
| Insulation Resistance At Maximum Operating Temp:                             |
| 200.0 megohm-microfarads   |
| Capacitance Value Per Section:   |
| 0.110 microfarads single section   |
| Nonderated Operating Temp:   |
| Between -55.0 degrees celsius and 85.0 degrees celsius                       |
| Thread Size:   |
| 0.138 inches   |
| Nonderated Continuous Voltage Rating And Type Per Section:                   |
| 1000.0 dc single section   |
| Tolerance Range Per Section:   |

1.0000

Metal

**Case Material:** 

**Terminal Surface Treatment:** 

20000.0 megohm-microfarads

-5.00 to 5.00 percent single section

**Insulation Resistance At Reference Temp:** 

**Dissipation Factor At Reference Tempurature In Percent:** 

Solder

## NSN 5910-00-556-9136

Paper Dielectric Fixed Capacitor - Page 2 of 2



|  | Ī | erm | inal | <b>Type</b> | And | Quantit | y: |
|--|---|-----|------|-------------|-----|---------|----|
|--|---|-----|------|-------------|-----|---------|----|

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0