

View Online at https://aerobasegroup.com/nsn/5910-00-557-3203

Body Style:

W/thd bushing mtg, terminals on opposite end

Reliability Indicator:

Not established

Width Across Flats:

0.625 inches

Terminal Length:

1.625 inches

Body Length:

1.250 inches

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

50.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.216 inches

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-330.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-500.0/+500.0 single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Power Factor At Reference Tempurature In Percent:

3.0000

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0