NSN 5910-00-558-6513

Plastic Dielectric Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/hsh/5910-00-558-6513 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.625 inches |
| Body Diameter: |
| 1.032 inches |
| Body Length: |
| 2.624 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 0.470 microfarads single section |
| Nonderated Operating Temp: |
| Between -65.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.1500 |
| Case Insulation Material: |
| Plastic |
| Test Data Document: |
| 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Specification Data: |
| 81349-mil-c-19978/5 government specification |
| Shelf Life: |

N/a

Unit Of Measure:

NSN 5910-00-558-6513

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0