NSN 5910-00-559-0540

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-559-0540

Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.625 inches
Body Length:
2.000 inches
Body Width:
1.062 inches
Body Height:
1.812 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.625 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Mounting Facility Type And Quantity:
4 unthreaded mounting holes
Capacitance Value Per Section:
0.200 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
2500.0 dc single section
Tolerance Range Per Section:
-20.00/+40.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
1.0000
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Meacure:

--

NSN 5910-00-559-0540

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



D !!		
Demil	ıtarız	ation:

No

Fiig:

A010b0