Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-567-1023

## Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.380 inches

## Body Length:

1.875 inches

#### **Body Width:**

1.250 inches

**Body Height:** 

1.125 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.172 inches and 0.202 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

### Between 2.115 inches and 2.145 inches

Schematic Diagram Designator:

Delta connected

## Mounting Facility Type And Quantity:

2 unthreaded mounting holes

### Section Quantity:

3

#### Features Provided:

Hermetically sealed case

#### **Capacitance Value Per Section:**

0.078 microfarads single section

## Nonderated Operating Temp:

Between 0.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

250.0 ac-rms all sections and 600.0 dc all sections

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent all sections

#### **Case Material:**

Ceramic or glass or metal

#### Insulation Resistance At Reference Temp:

1000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.7000

## **Terminal Type And Quantity:**

3 tab, solder lug

#### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0