

View Online at https://aerobasegroup.com/nsn/5910-00-577-1874

## **Body Style:**

W/o mtg facilities, radial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

## **Body Diameter:**

0.180 inches

#### **Body Length:**

0.650 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.375 inches

### **Terminal Diameter:**

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## **Capacitance Value Per Section:**

82.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-330.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

50000.0 megohms

## **Quality Factor At Reference Temp:**

1000.0000

### Test Data Document:

81349-milc20/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a



Demilitarization:

No

Fiig:

A010b0