NSN 5910-00-577-9250

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-577-9250					
Body Style:					
W/o mtg facilities, axial terminals					
Reliability Indicator:					
Not established					
Terminal Length:					
Between 1.625 inches and 2.625 inches					
Body Diameter:					
Between 0.190 inches and 0.210 inches					
Body Length:					
Between 0.594 inches and 0.656 inches					
Terminal Diameter:					
0.020 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Insulation Resistance At Maximum Operating Temp:					
6.0 megohm-microfarads					
Capacitance Value Per Section:					
0.010 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 100.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
400.0 dc single section					
Tolerance Range Per Section:					
5					
-20.00/+20.00 percent single section					
•					
-20.00/+20.00 percent single section					
-20.00/+20.00 percent single section Case Material:					
-20.00/+20.00 percent single section Case Material: Metal					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment:					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material:					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Paper					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Paper Case Insulation Material:					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Paper Case Insulation Material: Plastic					
-20.00/+20.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Paper Case Insulation Material: Plastic Terminal Type And Quantity:					

--

Unit Of Measure:

NSN 5910-00-577-9250

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0