NSN 5910-00-578-5168

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-578-5168 **Body Style:** W/o mtg facilities, terminal (s) on one surface Reliability Indicator: Not established **Body Length:** 1.312 inches **Body Width:** 0.625 inches **Body Height:** 1.375 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 50000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1000.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 6000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5910-00-578-5168

Paper Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0

Mil-std (military Standard):

Mil-c-25 spec.