## NSN 5910-00-581-8818

**Test Data Document:** 

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-581-8818

Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established
Body Length:
1.656 inches
Body Width:
1.500 inches
Body Height:
3.500 inches
Center To Center Distance Between Terminals Parallel To Width:
0.359 inches
Terminal Height From Body:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.000 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Section Quantity:
2
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
10.000 microfarads all sections
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.164 inches
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc all sections
Tolerance Range Per Section:
-20.00 to 20.00 percent 2nd section
Case Material:
Metal
Dissipation Factor At Reference Tempurature In Percent:
1.0000

18876-9003696 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## NSN 5910-00-581-8818

Paper Dielectric Fixed Capacitor - Page 2 of 2



<b>Terminal</b>	Type	And	Quantity:
-----------------	------	-----	-----------

4 wire hook/loop

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0