

View Online at <https://aerobasegroup.com/nsn/5910-00-583-0278>

Body Style:

W/thd bushing mtg, terminal (s) on one end

Reliability Indicator:

Not established

Body Diameter:

1.375 inches

Body Length:

2.250 inches

Schematic Diagram Designator:

One terminal common to each section

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

1300.0

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Un

Mounting Facility Type And Quantity:

1 threaded bushing

Section Quantity:

2

Features Provided:

Mounting hardware

Capacitance Value Per Section:

16.000 microfarads 2nd section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.875 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc 2nd section

Tolerance Range Per Section:

-10.00 to 50.00 percent 2nd section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

200.00

Dc Leakage At Reference Temp:

0.023 milliamperes

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0