## NSN 5910-00-592-2540

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-592-2540

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.322 inches
Body Length:
0.848 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Polarized
Capacitance Value Per Section:
200.000 microfarads single section
Nonderated Operating Temp:
Between -20.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
3.0 dc single section
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Case Material:  Metal
Metal
Metal  Capacitive Electrode Material:
Metal  Capacitive Electrode Material:  Aluminum
Metal  Capacitive Electrode Material:  Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms:
Metal  Capacitive Electrode Material:  Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms:  1.00
Metal  Capacitive Electrode Material:  Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms:  1.00  Dc Leakage At Reference Temp:
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms: 1.00  Dc Leakage At Reference Temp: 1.400 microamperes
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms: 1.00  Dc Leakage At Reference Temp: 1.400 microamperes  Case Insulation Material: Plastic
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms: 1.00  Dc Leakage At Reference Temp: 1.400 microamperes  Case Insulation Material:
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms: 1.00  Dc Leakage At Reference Temp: 1.400 microamperes  Case Insulation Material: Plastic  Terminal Type And Quantity:
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms: 1.00  Dc Leakage At Reference Temp: 1.400 microamperes  Case Insulation Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms: 1.00  Dc Leakage At Reference Temp: 1.400 microamperes  Case Insulation Material: Plastic  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
Metal  Capacitive Electrode Material: Aluminum  Equivalent Series Resistance At Reference Tempurature In Ohms:  1.00  Dc Leakage At Reference Temp:  1.400 microamperes  Case Insulation Material:  Plastic  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a

No

## NSN 5910-00-592-2540

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0