NSN 5910-00-603-5900

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-603-5900

Body Style: W/mtg bracket, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.750 inches **Body Diameter:** 0.750 inches **Body Length:** 1.875 inches **Body Width:** 0.750 inches **Body Height:** 0.750 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 100000.0 megohm-microfarads **Capacitance Value Per Section:** 0.2017 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -140.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -0.0 to 30.0 single section **Tolerance Range Per Section:** -0.30 to 0.30 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 1000000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:**

0.0200

NSN 5910-00-603-5900 Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Terminal Surface Treatment: |
|-----------------------------|
| Solder |
| Dielectric Material: |
| Plastic polystyrene |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A010b0