

View Online at <https://aerobasegroup.com/nsn/5910-00-605-5733>

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Body Diameter:

2.000 inches

Body Length:

2.400 inches

Continuous Current Rating In Amps:

50.0

Terminal Diameter:

0.250 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

2 threaded bushing

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

1.100 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

1.000 inches

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 ac-rms single section and 1000.0 dc single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

450.0 megohms

Dissipation Factor At Reference Temperature In Percent:

1.0000

Test Data Document:

81205-27-10387 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0