NSN 5910-00-608-6524

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-608-6524 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.625 inches **Body Diameter:** 1.010 inches **Body Length:** 2.594 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 3.300 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 picofarads single section Case Material: Metal **Insulation Resistance At Reference Temp:** 4000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Case Insulation Material:** Plastic **Test Data Document:** 81349-milc39022/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-00-608-6524

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0