NSN 5910-00-615-5087

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-615-5087

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:

0.750 inches

Body Length: 1.312 inches

Body Width:

0.725 inches

Body Height:

2.000 inches

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Internal Electrical Connection Type:

Inserted tab

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

0.250 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

6000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-00-615-5087

Paper Dielectric Fixed Capacitor - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-c-25/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0