

View Online at <https://aerobasegroup.com/nsn/5910-00-617-6647>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0001

Width Across Flats:

0.250 inches

Body Length:

0.562 inches

Continuous Current Rating In Amps:

5.0

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware and hermetically sealed case

Capacitance Value Per Section:

100.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.0000

Power Factor At Reference Temperature In Percent:

12.0000

Quality Factor At Reference Temp:

35.0000

Special Features:

Selected item as per drawing no. 0n143242

Test Data Document:

98230-0n143242 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0