

NSN 3910-00-621-9212 Plastic Dielectric Fixed Capacitor - Page 1 of 2	AGTUDAS Grou
View Online at https://aerobasegroup.com/nsn/5910-00-621-9212	
Body Style:	
W/o mtg facilities, axial terminals	
Reliability Indicator:	
Not established	
Terminal Length:	
1.625 inches	
Body Diameter:	
0.463 inches	
Body Length:	
1.125 inches	
Terminal Diameter:	
0.032 inches	
Schematic Diagram Designator:	
Electrod (s) grounded to case, w/gnd terminal	
Internal Electrical Connection Type:	
Extended foil	
Features Provided:	

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

0.220 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

25000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Dielectric Material:

Paper and plastic polyethylene terephthalate

Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-00-621-9212

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
81349-mil-c-19978/19 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0