## NSN 5910-00-622-0041

**Body Style:** 

**Specification Data:** 

81349-mil-c-19978/2b government specification

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-622-0041

W/o mtg facilities, axial terminals	
Reliability Indicator:	
Not established	
Terminal Length:	
2.000 inches	
Body Diameter:	
0.750 inches	
Body Length:	
2.250 inches	
Terminal Diameter:	
0.040 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Internal Electrical Connection Type:	
Extended foil	
Insulation Resistance At Maximum Operating Temp:	
250.0 megohms	
Capacitance Value Per Section:	
0.015 microfarads single section	
Nonderated Operating Temp:	
Between -65.0 degrees celsius and 125.0 degrees celsius	
Nonderated Continuous Voltage Rating And Type Per Section:	
5000.0 dc single section	
Tolerance Range Per Section:	
-10.00/+10.00 percent single section	
Case Material:	
Ceramic	
Insulation Resistance At Reference Temp:	
25000.0 megohms	
Dissipation Factor At Reference Tempurature In Percent:	
1.000	
Terminal Surface Treatment:	
Solder	
Dielectric Material:	
Paper and plastic polyethylene terephthalate	
Test Data Document:	
81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
2 uninsulated wire lead	

## NSN 5910-00-622-0041

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0