Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-622-1880

Body Style:

W/mtg ta (s), terminal(s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.281 inches

Body Diameter:

Between 2.469 inches and 2.531 inches

Mounting Slot Width:

0.176 inches

Body Length:

Between 4.063 inches and 4.187 inches

Continuous Current Rating In Amps:

16.6

Center To Center Distance Between Terminals Parallel To Diameter:

Between 1.109 inches and 1.241 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

1.0

Electrical Polarization:

Polarized

Mounting Facility Type And Quantity:

3 mounting slots

Features Provided:

Mounting hardware

Capacitance Value Per Section:

10400.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 65.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.045

Electrolytic Fixed Capacitor - Page 2 of 2



Dc Leakage At Reference Temp: 2.000 microamperes **Case Insulation Material:** Plastic **Special Features:** Mtg slots spaced 120 degrees apart Terminal Type And Quantity: 2 threaded hole Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A010b0