Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-624-9785

# **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

2.250 inches

# **Body Diameter:**

0.468 inches

#### **Body Length:**

0.688 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

# Impedance At Minimum Operating Tempurature In Ohms:

# 65.0

**Electrical Polarization:** 

Polarized

# **Features Provided:**

Hermetically sealed case

# **Capacitance Value Per Section:**

100.000 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

#### **Tolerance Range Per Section:**

-15.00/+20.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Tantalum

# Equivalent Series Resistance At Reference Tempurature In Ohms:

4.00

# Dc Leakage At Reference Temp:

2.000 microamperes

#### **Test Data Document:**

56289-3710b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

# NSN 5910-00-624-9785

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0