## NSN 5910-00-626-9809

W/mtg tabs/flanges, terminal (s) on one surface

**Body Style:** 

**Reliability Indicator:** 

2 standoff, threaded stud

Not established

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-626-9809

**Body Length:** 9.000 inches **Body Width:** 4.375 inches **Body Height:** 8.125 inches **Center To Center Distance Between Terminals Parallel To Length:** 5.000 inches **Terminal Diameter:** 0.500 inches **Terminal Height From Body:** 3.000 inches **Unthreaded Mounting Hole Diameter:** 0.287 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 10.250 inches **Schematic Diagram Designator:** No common or grounded electrode (s) Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches **Mounting Facility Type And Quantity:** 4 unthreaded mounting holes **Capacitance Value Per Section:** 2.500 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 62.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 13500.0 ac-rms single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 12000.0 megohms **Power Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Type And Quantity:** 

## NSN 5910-00-626-9809

Paper Dielectric Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0