## NSN 5910-00-628-6223

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-628-6223

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established

Terminal Length: 1.625 inches

**Body Diameter:** 

0.812 inches

**Body Length:** 

2.188 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

20.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.560 microfarads single section

**Nonderated Operating Temp:** 

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

Case Material:

Metal

**Insulation Resistance At Reference Temp:** 

25000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Paper and plastic polyethylene terephthalate

**Case Insulation Material:** 

Plastic

**Test Data Document:** 

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-628-6223

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-c-19978/19 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0