

View Online at <https://aerobasegroup.com/nsn/5910-00-632-3568>

**Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.625 inches

**Body Diameter:**

0.750 inches

**Body Length:**

2.125 inches

**Terminal Diameter:**

0.032 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Internal Electrical Connection Type:**

Extended foil

**Mounting Facility Type And Quantity:**

1 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

20.0 megohm-microfarads

**Capacitance Value Per Section:**

0.470 microfarads single section

**Nonderated Operating Temp:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

600.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

25000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Terminal Surface Treatment:**

Solder

**Dielectric Material:**

Paper and plastic polyethylene terephthalate

**Test Data Document:**

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-19978/20 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0