AeroBase Group

View Online at https://aerobasegroup.com/nsn/5910-00-632-7824

| Thread Class: 2b Body Style: Concentric Flange Diameter: 1.690 inches Overall Height: 4.410 inches Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: Unc |
|---|
| Body Style: Concentric Flange Diameter: 1.690 inches Overall Height: 4.410 inches Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 |
| Concentric Flange Diameter: 1.690 inches Overall Height: 4.410 inches Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Flange Diameter:1.690 inchesOverall Height:4.410 inches4.410 inchesShaft Diameter:0.380 inches single shaftShaft Length:0.300 inches single shaftAlternating Current Rating In Amps:14.0Body Height:4.000 inches2.120 inchesQuality Factor At 25 Deg Celsius:1000.0Mounting Facility Screw Thread Series Designator: |
| 1.690 inches Overall Height: 4.410 inches Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Overall Height: 4.410 inches Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 4.410 inches Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Shaft Diameter: 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 0.380 inches single shaft Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Shaft Length: 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 0.300 inches single shaft Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Alternating Current Rating In Amps: 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 14.0 Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Body Height: 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 4.000 inches Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Overall Diameter: 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 2.120 inches Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| Quality Factor At 25 Deg Celsius: 1000.0 Mounting Facility Screw Thread Series Designator: |
| 1000.0 Mounting Facility Screw Thread Series Designator: |
| Mounting Facility Screw Thread Series Designator: |
| |
| Unc |
| |
| Adjustment Device Rotation: |
| 25.0 turns clockwise |
| Adjustment Device Torque: |
| 2.100 inch-pounds |
| Mounting Facility Type And Quantity: |
| 6 threaded hole |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Thread Size: |
| 0.138 inches |
| Shaft Type: |
| Round, slotted single shaft |
| Capacitance Range In Picofarads: |
| +5.0/+465.0 single section |
| Nonderated Voltage Rating And Type: |
| 6000.0 ac rms single section |
| |
| Adjustment Device Drive Type And Quantity: |
| - |
| Adjustment Device Drive Type And Quantity: |



Terminal Type And Quantity:

3 threaded hole

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0