NSN 5910-00-642-6759

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-642-6759

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.625 inches
Body Length:
1.188 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Inserted tab
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
10.0 megohm-microfarads
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
18000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder

Plastic

Case Insulation Material:

NSN 5910-00-642-6759

Paper Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/1f government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0