## NSN 5910-00-643-6382

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-643-6382 **Body Style:** W/o mtg facilities, terminals on opposite surfaces Reliability Indicator: Not established **Terminal Length:** 1.250 inches **Body Length:** 1.438 inches **Body Width:** 0.375 inches **Body Height:** 0.719 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 600.0 megohm-microfarads **Capacitance Value Per Section:** 50000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -20.00 to 20.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 6000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.80000 **Test Data Document:** 81349-mil-c-91 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5910-00-643-6382

Paper Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0