

View Online at <https://aerobasegroup.com/nsn/5910-00-643-8835>

**Body Style:**

W/thd bushing mtg, terminals on opposite end

**Reliability Indicator:**

Not established

**Width Across Flats:**

Between 0.298 inches and 0.328 inches

**Terminal Length:**

0.219 inches

**Body Length:**

Between 0.610 inches and 0.640 inches

**Terminal Diameter:**

0.055 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

56.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.216 inches

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

-650.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

1000.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-120.0/+120.0 single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Power Factor At Reference Temperature In Percent:**

3.000

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 wire hook/loop

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0