

View Online at https://aerobasegroup.com/nsn/5910-00-644-0606

### **Body Style:**

W/thd mtg studs, axial terminals

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.628 inches

### **Body Diameter:**

0.670 inches

#### **Body Length:**

1.625 inches

#### **Body Width:**

1.065 inches

### **Body Height:**

0.670 inches

#### **Terminal Diameter:**

0.032 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.875 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Internal Electrical Connection Type:

Extended foil

## Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

2 threaded mounting studs

## **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

#### Capacitance Value Per Section:

0.270 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Thread Size:**

0.138 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

Paper Dielectric Fixed Capacitor - Page 2 of 2



## Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Paper

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

### Fiig:

A010b0