NSN 5910-00-644-0792



Air Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-644-0792

Thread Class:
Any acceptable
Body Style:
Plate-meshing
Overall Length:
1.844 inches
Overall Height:
1.219 inches
Overall Width:
0.938 inches
Shaft Diameter:
Any acceptable single shaft
Shaft Length:
0.219 inches single shaft
Body Length:
1.625 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.656 inches
Mounting Facility Screw Thread Series Designator:
Unc
In all a some Tomas
Inclosure Type:
Uninclosed
Uninclosed
Uninclosed Tuning Characteristic:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.112 inches
Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.112 inches Shaft Type: Round, slotted single shaft Capacitance Range In Picofarads:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.112 inches Shaft Type: Round, slotted single shaft
Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 160.0 degrees counterclockwise Adjustment Device Torque: Between 2.500 inch-ounces and 10.000 inch-ounces Mounting Facility Type And Quantity: 2 threaded hole Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.112 inches Shaft Type: Round, slotted single shaft Capacitance Range In Picofarads:

1 shaft

Adjustment Device Drive Type And Quantity:

NSN 5910-00-644-0792

Air Dielectric Variable Capacitor - Page 2 of 2



М			

Ceramic insulation supporting

Terminal Type And Quantity:

2 pin and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0