NSN 5910-00-644-6289

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-644-6289

В	ody Style:
W	o mtg facilities, axial terminals
Re	eliability Indicator:
No	ot established
Te	erminal Length:
1.0	625 inches
В	ody Diameter:
0.3	375 inches
В	ody Length:
0.9	937 inches
В	ody Width:
0.3	375 inches
В	ody Height:
0.3	375 inches
Te	erminal Diameter:
0.0	032 inches
Sc	chematic Diagram Designator:
No	common or grounded electrode (s)
In	ternal Electrical Connection Type:
Ex	ctended foil
Fe	eatures Provided:
Не	ermetically sealed case
In	sulation Resistance At Maximum Operating Temp:
15	0.0 megohms
Ca	apacitance Value Per Section:
15	000.000 picofarads single section
No	onderated Operating Temp:
Ве	etween -55.0 degrees celsius and 125.0 degrees celsius
No	onderated Continuous Voltage Rating And Type Per Section:
40	0.0 dc single section
To	olerance Range Per Section:
-1	0.00 to 10.00 percent single section
Ca	ase Material:
Me	etal
In	sulation Resistance At Reference Temp:
18	000.0 megohms
Di	ssipation Factor At Reference Tempurature In Percent:
1.0	0000
Te	erminal Surface Treatment:
Sc	older

Plastic

Case Insulation Material:

NSN 5910-00-644-6289

Paper Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/1k government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0