

View Online at https://aerobasegroup.com/nsn/5910-00-644-6561

### **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.250 inches

## **Body Diameter:**

0.225 inches

#### **Body Length:**

0.687 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.375 inches

**Terminal Diameter:** 

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

1500.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Ceramic

Insulation Resistance At Reference Temp:

20000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.5000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-11015/4c government specification

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0