NSN 5910-00-648-7333

Body Style:

Ceramic Dielectric Variable Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-00-648-7333



Rotary **Body Length:** 1.125 inches **Body Width:** 0.656 inches **Body Height:** 0.375 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Unthreaded Mounting Hole Diameter:** 0.145 inches and 0.145 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 0.859 inches **Dissipation Factor At 25 Deg Celsius In Percent: Inclosure Type:** Encapsulated **Adjustment Device Rotation:** 360.0 degrees clockwise **Adjustment Device Torque:** Between 4.000 inch-ounces and 24.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 unthreaded hole **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +1.5 to 7.0 single section **Nonderated Voltage Rating And Type:** 500.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.50 single section Material: Ceramic base **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a

NSN 5910-00-648-7333

Ceramic Dielectric Variable Capacitor - Page 2 of 2



	• •					
ın	18	<i>(</i>)+	Me	20	III	ω.

--

Demilitarization:

No

Fiig:

A096a0