## NSN 5910-00-648-7856

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-648-7856
Body Style:
Rotary
Body Length:
0.750 inches
Body Width:
0.531 inches
Body Height:
0.234 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
-750.0 single section
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-200.0 to 200.0 single section
Unthreaded Mounting Hole Diameter:
0.093 inches and 0.093 inches
Quality Factor At 25 Deg Celsius:
200.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.312 inches
Inclosure Type:
Encapsulated
Adjustment Device Torque:
Between 2.000 inch-ounces and 8.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
10.0 gigohms
Mounting Facility Type And Quantity:
2 unthreaded hole
Capacitance Range In Picofarads:
+5.0 to 30.0 single section
Nonderated Voltage Rating And Type:
350.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.38 single section
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5910-00-648-7856

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Fiig:

A096a0