## NSN 5910-00-648-9715

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-648-9715

Body Style:				
W/mtg tabs/flanges, terminal (s) on one surface				
Reliability Indicator:				
Not established				
Terminal Length:				
4.312 inches				
Body Length:				
1.750 inches				
Body Width:				
1.250 inches				
Body Height:				
0.725 inches				
Unthreaded Mounting Hole Diameter:				
0.188 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
2.062 inches				
Schematic Diagram Designator:				
Electrod (s) grounded to case				
Mounting Facility Type And Quantity:				
2 unthreaded mounting holes				
Features Provided:				
Hermetically sealed case				
Capacitance Value Per Section:				
4.000 microfarads single section				
Nonderated Operating Temp:				
Between -55.0 degrees celsius and 85.0 degrees celsius				
Nonderated Continuous Voltage Rating And Type Per Section:				
150.0 dc single section				
Tolerance Range Per Section:				
-6.00/+15.00 percent single section				
Case Material:				
Metal				
Insulation Resistance At Reference Temp:				
2000.00 megohms				
Dissipation Factor At Reference Tempurature In Percent:				
1.250				
Terminal Surface Treatment:				
Solder				

Shelf Life:

N/a

**Terminal Type And Quantity:**1 insulated wire lead w/terminal lug

## NSN 5910-00-648-9715

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0