

View Online at <https://aerobasegroup.com/nsn/5910-00-649-3118>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Body Length:**

Between 1.719 inches and 1.844 inches

**Body Width:**

1.000 inches

**Body Height:**

0.938 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.063 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.125 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

20.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Range Per Section:**

-10.00/+100.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

18.000

**Dc Leakage At Reference Temp:**

0.400 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0