

View Online at https://aerobasegroup.com/nsn/5910-00-660-7618

### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

# Terminal Length:

Between 0.350 inches and 0.440 inches

### **Body Diameter:**

Between 0.690 inches and 0.810 inches

#### **Body Length:**

Between 1.690 inches and 1.810 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Mounting Facility Screw Thread Series Designator:

Unc

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

200.0 megohm-microfarads

### **Capacitance Value Per Section:**

10000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Thread Size:

0.164 inches

# Nonderated Continuous Voltage Rating And Type Per Section:

5000.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### Case Material:

Glass

### Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

# Power Factor At Reference Tempurature In Percent:

0.9000

### **Dielectric Material:**

Plastic

### **Terminal Type And Quantity:**

2 threaded stud

Shelf Life:

N/a

### Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0