NSN 5910-00-666-6388

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-666-6388
Thread Class:
2a
Body Style:
Piston
Overall Length:
1.940 inches
Bushing Diameter:
0.250 inches
Shaft Diameter:
0.112 inches single shaft
Bushing Length:
0.281 inches
Shaft Length:
0.375 inches single shaft
Body Length:
1.125 inches
Overall Diameter:
0.470 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-800.0/+800.0 single section
Quality Factor At 25 Deg Celsius:
500.0
Fragility Factor:
Moderately rugged
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 10.000 inch-ounces
Bushing Shape:
Round
Mounting Facility Type And Quantity:
1 threaded bushing
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.250 inches
Shaft Type:
Round, slotted single shaft
Canacitance Range In Picofarade:

+9.0/+16.0 single section

NSN 5910-00-666-6388

Glass Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
300.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Material:
Glass inclosure
Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0