## NSN 5910-00-666-7252

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-666-7252 **Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** Between 0.510 inches and 0.615 inches **Body Length:** Between 0.116 inches and 0.196 inches **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.270 inches and 0.390 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohm-microfarads **Capacitance Value Per Section:** 2200.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Range Per Section:** -20.00/+100.00 percent single section **Insulation Resistance At Reference Temp:** 50000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 2.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A010b0