

View Online at <https://aerobasegroup.com/nsn/5910-00-666-7619>

Body Style:

Rotary

Overall Length:

0.750 inches

Terminal Length:

0.360 inches

Overall Height:

0.230 inches

Overall Width:

0.530 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-750.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-120.0 to 120.0 single section

Center To Center Distance Between Terminals Parallel To Length:

0.390 inches

Unthreaded Mounting Hole Diameter:

0.124 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.310 inches

Quality Factor At 25 Deg Celsius:

500.0

Fragility Factor:

Moderately rugged

Terminal Width:

0.090 inches

Terminal Thickness:

0.012 inches

Inclosure Type:

Encased

Adjustment Device Torque:

Between 2.000 inch-ounces and 8.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+5.0 to 30.0 single section

Nonderated Voltage Rating And Type:

350.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.05 single section

Material:

Steatite base

Precious Material And Location:

Rotor surfaces and stator surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0