NSN 5910-00-666-7990

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-666-7990 **Body Style:** Rotary **Body Length:** 1.219 inches **Body Width:** 0.938 inches **Body Height:** 0.706 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -650.0 single section **Unthreaded Mounting Hole Diameter:** 0.112 inches and 0.112 inches **Dissipation Factor At 25 Deg Celsius In Percent:** 0.2 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.656 inches **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Encapsulated **Adjustment Device Rotation:** 360.0 degrees clockwise **Adjustment Device Torque:** Between 0.250 inch-ounces and 2.750 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 threaded hole **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.112 inches

Capacitance Range In Picofarads:

+20.0 to 120.0 single section

Nonderated Voltage Rating And Type:

600.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Special Features:

Mtg holes tapped 0.188 in.Deep

NSN 5910-00-666-7990

Ceramic Dielectric Variable Capacitor - Page 2 of 2



late	

Ceramic base

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0