

View Online at <https://aerobasegroup.com/nsn/5910-00-666-9171>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Mounting Slot Width:

0.156 inches

Body Length:

1.312 inches

Body Width:

0.766 inches

Body Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.938 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Type And Quantity:

1 mounting slots

Section Quantity:

2

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

600.0 megohms

Capacitance Value Per Section:

10000.000 picofarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc all sections

Tolerance Range Per Section:

-10.00 to 20.00 percent 2nd section

Case Material:

Metal

Insulation Resistance At Reference Temp:

6000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0