Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-667-4867

## **Body Style:**

W/thd mtg studs, axial terminals

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.400 inches

#### **Body Length:**

0.874 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.625 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Internal Electrical Connection Type:

Inserted tab

# Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

2 threaded mounting studs

# **Features Provided:**

Hermetically sealed case

#### Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

#### Capacitance Value Per Section:

0.100 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Thread Size:

0.138 inches

# Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Surface Treatment:**

Solder



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0